












Endless Eslinga plana

Parámetros técnicos

Color	Código de colores de acuerdo	Carga límite de trabajo con honda 1 cincha							Carga límite de trabajo con honda 2 correas			
		ascensor	ascensor	Ø					Straight 45 y	Ascensor ahogado	Elevación recta de	Ascensor ahogado
-	-	-	-	0-7	7-45	45-60	Up to 45	45-60	-	-	-	-
-	-											
-	-	1.0	0.8	2.0	1.4	1.0	0.7	0.5	1.4	1.12	1.0	0.8
púrpura	WLL 1T	1.000	800	2.000	1.400	1.000	700	500	1.400	1.120	1.000	800
verde	WLL 2T	2.000	1.600	4.000	2.800	2.000	1.400	1.000	2.800	2.240	2.000	1.600
amarillo	WLL 3T	3.000	2.400	6.000	4.200	3.000	2.100	1.500	4.200	3.360	3.000	2.400
Gris	WLL 4T	4.000	3.200	8.000	5.600	4.000	2.800	2.000	5.600	4.480	4.000	3.200
rojo	WLL 5T	5.000	4.000	10.000	7.000	5.000	3.500	2.500	7.000	5.600	5.000	4.000
marrón	WLL 6T	6.000	4.800	12.000	8.400	6.000	4.200	3.000	8.400	6.720	6.000	4.800
azul	WLL 8T	8.000	6.400	16.000	11.200	8.000	5.600	4.000	11.200	8.960	8.000	6.400
naranja	WLL 10T	10.000	8.000	20.000	14.000	10.000	7.000	5.000	14.000	11.000	10.000	8.000
naranja	WLL 20T	20.000	16.000	40.000	28.000	20.000	14.000	10.000	28.000	22.400	20.000	16.000