

Serie ES Cadena Polipasto 500kg a 5ton

| Una velocidad |                 |                                  |              | Motor de elevación |                              | Fuente De Alimentación |             |                 | Motor Viajar |                              |         |
|---------------|-----------------|----------------------------------|--------------|--------------------|------------------------------|------------------------|-------------|-----------------|--------------|------------------------------|---------|
| modelo        | Capacidad (Ton) | Velocidad de elevación (m / min) | Cadena Falls | Poder (KW)         | Rotación velocidad (r / min) | fase                   | Tensión (V) | Frecuencia (Hz) | Poder (KW)   | Rotación velocidad (r / min) | I-haz   |
| HHBD0.5-01    | 0.5             | 7.8                              | 1            | 0.75               | 1440                         | 3                      | 200V-690V   | 50/60           | 0.12         | 1440                         | 58-130  |
| HHBD01-01     | 1               | 6.8                              | 1            | 1.5                | 1440                         | 3                      | 200V-690V   | 50/60           | 0.4          | 1440                         | 80-160  |
| HHBD01-02     | 1               | 3.9                              | 2            | 0.75               | 1440                         | 3                      | 200V-690V   | 50/60           | 0.4          | 1440                         | 80-160  |
| HHBD02-01     | 2               | 6.8                              | 1            | 3.0                | 1440                         | 3                      | 200V-690V   | 50/60           | 0.4          | 1440                         | 82-178  |
| HHBD02-02     | 2               | 3.4                              | 2            | 1.5                | 1440                         | 3                      | 200V-690V   | 50/60           | 0.4          | 1440                         | 82-178  |
| HHBD03-01     | 3               | 5.6                              | 1            | 3.0                | 1440                         | 3                      | 200V-690V   | 50/60           | 0.4          | 1440                         | 100-180 |
| HHBD03-02     | 3               | 3.4                              | 2            | 3.0                | 1440                         | 3                      | 200V-690V   | 50/60           | 0.4          | 1440                         | 100-180 |
| HHBD03-03     | 3               | 2.2                              | 3            | 1.5                | 1440                         | 3                      | 200V-690V   | 50/60           | 0.4          | 1440                         | 110-178 |
| HHBD05-02     | 5               | 2.8                              | 2            | 3.0                | 1440                         | 3                      | 200V-690V   | 50/60           | 0.75         | 1440                         | 110-180 |

Motor Grado del aislamiento: F  
Opción Control de Voltaje: 24V, 36V, 48V

| velocidad Dual |                 |                                  |              | Motor de elevación |                              | Fuente De Alimentación |             |                 | Motor Viajar |                              |         |
|----------------|-----------------|----------------------------------|--------------|--------------------|------------------------------|------------------------|-------------|-----------------|--------------|------------------------------|---------|
| modelo         | Capacidad (Ton) | Velocidad de elevación (m / min) | Cadena Falls | Poder (KW)         | Rotación velocidad (r / min) | fase                   | Tensión (V) | Frecuencia (Hz) | Poder (KW)   | Rotación velocidad (r / min) | I-haz   |
| HHBD01-01DS    | 1               | 7.2/2.4                          | 1            | 1.5/0.6            | 2830/980                     | 3                      | 200V-690V   | 50/60           | 0.4          | 1440                         | 80-160  |
| HHBD02-01DS    | 2               | 6.8/2.3                          | 1            | 4.0/1.8            | 2830/980                     | 3                      | 200V-690V   | 50/60           | 0.4          | 1440                         | 82-178  |
| HHBD02-02DS    | 2               | 3.6/1.2                          | 2            | 1.5/0.6            | 2830/980                     | 3                      | 200V-690V   | 50/60           | 0.4          | 1440                         | 82-178  |
| HHBD03-01DS    | 3               | 5.6/1.9                          | 1            | 4.0/1.8            | 2830/980                     | 3                      | 200V-690V   | 50/60           | 0.4          | 1440                         | 100-180 |
| HHBD03-02DS    | 3               | 3.4/1.2                          | 2            | 4.0/1.8            | 2830/980                     | 3                      | 200V-690V   | 50/60           | 0.4          | 1440                         | 100-180 |
| HHBD03-03DS    | 3               | 3.4/1.1                          | 3            | 1.5/0.6            | 2830/980                     | 3                      | 200V-690V   | 50/60           | 0.4          | 1440                         | 110-178 |
| HHBD05-02DS    | 5               | 2.2/0.8                          | 2            | 4.0/1.8            | 2830/980                     | 3                      | 200V-690V   | 50/60           | 0.75         | 1440                         | 110-180 |