

## MPT-C serie Empuje Trolley

### Parámetros técnicos

modelo	Capacidad (Ton)	Brida Ancho (mm)	Dimensiones (mm)							N.W. (kg)	El radio mínimo de curva (m)
			M	la	B	C	D	H	S		
MPT-C050	0.5	50-152	236	194	176	28	75	30	32	6	0.8
MPT-C050L		50-203	286							6.5	
MPT-C100	1	64-203	303	236	196	32	96	38	40	11.5	0.9
MPT-C100L		64-305	405							13	
MPT-C150	1.5	74-203	310	250	210	36	102	38	45	14	1
MPT-C150L		74-305	412							16	
MPT-C200	2	88-203	317	268	226	42	109	38	52	18	1
MPT-C200L		88-305	419							20	
MPT-C300	3	100-203	333	322	266	52	124	40	63	30	1.2
MPT-C300L		100-305	435							34	
MPT-C500	5	124-203	355	362	301	62	142	42	74	44	1.3
MPT-C500L		124-305	475							50	
MPT-C800	8	124-203	372	426	388	72	185	45	110	73	2
MPT-C800L		124-305	474							79	
MPT-C1000	10	136-203	378	442	396	72	190	45	110	82	2
MPT-C1000L		124-305	480							89	
MPT-C1500	15	136-203	449	555	498	95	236	65	135	157	3.5
MPT-C1500L		136-305	551							164	
MPT-C2000	20	136-203	449	555	498	95	233	58	135	159	3.5
MPT-C2000L		136-305	551							167	